

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (previously presented) A planar-magnetic transducer comprising:

at least one thin film vibratable diaphragm with a first surface side and a second surface side, including a predetermined active region, said predetermined active region including a predetermined conductive surface area for converting an input electrical signal into a corresponding acoustic output;

primary magnetic structure including at least three elongated magnets placed adjacent and substantially parallel to each other with said magnets being of high energy and each having an energy product of greater than 25 mega Gauss Oersteds (MGO) which results in strong interaction between adjacent magnets; and

a mounting support structure coupled to the primary magnetic structure and the diaphragm to capture the diaphragm, hold it in a predetermined state of tension and space it at a predetermined distance from the primary magnetic structure adjacent one of the surface sides of the diaphragm; said conductive surface area including elongate conductive paths running substantially parallel to said magnets;

the mounting support structure, the at least three magnets of the primary magnetic structure, and the diaphragm having coordinated compositions and being cooperatively configured and positioned in predetermined spaced apart relationships wherein (i) the mounting support structure stabilizes the diaphragm in a static configuration at the predetermined tension which remains stable over and between extended periods of use, despite occurrence of dynamic conditions in response to extreme high energy forces driving the diaphragm to audio output, and (ii) the high energy magnetic forces interacting between the at least three magnets do not interfere with the predetermined tension of the diaphragm;

said planar-magnetic transducer being operable as a single-ended planar-magnetic transducer.

2. (original) A planar-magnetic transducer as set forth in claim 1 wherein the high energy magnets comprise neodymium.

3. (previously presented) A planar-magnetic transducer as set forth in claim 1 wherein the high energy magnets are neodymium magnets with an energy rating of at least 34 MGO.

4. (original) A planar-magnetic transducer as set forth in claim 1, wherein the at least one thin film vibratable diaphragm includes a predetermined active region of less than 150 square inches, said predetermined active region including a predetermined conductive surface area for converting the input electrical signal into the corresponding acoustic output having an upper audio bandwidth extending down to a low range audio frequency.

5. (original) A planar-magnetic transducer as set forth in claim 4 wherein said transducer diaphragm has a vibratable area and a fundamental resonant frequency representing approximately the lowest potential cutoff frequency of operation,

the vibratable area and lowest cutoff frequency of operation of the planar-magnetic transducer falling into the unique range of

$$Fr < (2000/\sqrt{A})$$

wherein (Fr) equals the fundamental resonant frequency of the transducer in Hertz and (A) equals the vibratable area of the transducer diaphragm in square inches.

6. (original) A planar-magnetic transducer as set forth in claim 4 wherein:

said transducer diaphragm has a vibratable area and a centered gap between the magnetic structure and the diaphragm measured at the center of the diaphragm,

said transducer has a fundamental resonant frequency representing approximately the lowest potential cutoff frequency of operation, and

the vibratable area and lowest cutoff frequency of operation of the planar-magnetic transducer are in the range of

$$Fr < (1500/\sqrt{A} \text{ G})$$

wherein (Fr) equals the fundamental resonant frequency of the transducer in Hertz and (A) equals the vibratable area of the transducer diaphragm in square inches and (G) equals the magnet to diaphragm gap measured in millimeters at the center of the transducer diaphragm.

7. (original) A planar-magnetic transducer as set forth in claim 4 wherein:
 said transducer diaphragm has a vibratable area and a centered gap between the magnetic structure and the diaphragm measured at the center of the diaphragm,
 said transducer has a fundamental resonant frequency representing approximately the lowest potential cutoff frequency of operation, and
 the vibratable area and lowest cutoff frequency of operation of the planar-magnetic transducer are in the range of

$$Fr < (1000/\sqrt{A} \text{ G})$$

wherein (Fr) equals the fundamental resonant frequency of the transducer in Hertz and (A) equals the vibratable area of the transducer diaphragm in square inches and (G) equals the magnet to diaphragm gap measured in millimeters at the center of the transducer diaphragm.

8. (previously presented) A planar-magnetic transducer as set forth in claim 4 wherein:

said transducer diaphragm has a vibratable area with a length and a width dimension wherein the width dimension is the lesser of the length and width dimensions,

said transducer has a fundamental resonant frequency representing approximately the lowest potential cutoff frequency of operation, and

the width of the vibratable area and lowest cutoff frequency of operation of the planar-magnetic transducer are in the range of

$$Fr < (1000/W)$$

wherein (Fr) equals the fundamental resonant frequency of the transducer in Hertz and (W) equals width dimension of the vibratable area of the transducer diaphragm in inches.

9. (original) A planar-magnetic transducer as set forth in claim 4 wherein:
said transducer diaphragm has a vibratable area with a width dimension less than a length dimension,

the transducer further has a gap dimension between the magnetic structure and the diaphragm and said gap dimension measured at the center of the diaphragm,

said transducer has a fundamental resonant frequency representing approximately the lowest potential cutoff frequency of operation, and

the width of the vibratable area and lowest cutoff frequency of operation of the planar-magnetic transducer are in the range of $Fr < (800/W)/G$;

wherein (Fr) equals the fundamental resonant frequency of the transducer in Hertz and (W) equals width dimension of the vibratable area of the transducer diaphragm in inches and (G) equals the magnet to diaphragm gap measured in millimeters at the center of the transducer diaphragm.

10. (original) A planar-magnetic transducer as set forth in claim 4 wherein the predetermined active diaphragm region has a total surface area of less than 100 square inches.

11. (original) A planar-magnetic transducer as set forth in claim 4 wherein the predetermined active diaphragm region has a total surface area of less than 80 square inches.

12. (original) A planar-magnetic transducer as set forth in claim 4 wherein the predetermined active diaphragm region has a total surface area of less than 60 square inches while having an operating resonant frequency of less than 400 Hz.

13. (original) A planar-magnetic transducer as set forth in claim 12 having an operating resonant frequency of less than 300 Hz.

14. (original) A planar-magnetic transducer as set forth in claim 4 wherein the

predetermined active diaphragm region has a total surface area of less than 20 square inches while having an operating resonant frequency of less than 400 Hz.

15. (original) A planar-magnetic transducer as set forth in claim 14 having an operating resonant frequency of less than 300 Hz.

16. (original) A planar-magnetic transducer as set forth in claim 4 wherein the predetermined active diaphragm region has a total surface area of less than 9 square inches while having an operating resonant frequency of less than 900 Hz.

17. (original) A planar-magnetic transducer as set forth in claim 4 further comprising a plurality of said transducers intercoupled as a line source of serially mounted transducers which form a loudspeaker taller than one transducer.

18. (original) A planar-magnetic transducer as set forth in claim 1 further comprising at least one spacer structure positioned and abutting between at least two adjacent high energy magnets to eliminate the effect of magnetic attraction forces from potentially reducing the predetermined distance between at least two of the high energy magnets so the high energy magnetic forces do not interfere with the predetermined tension of the diaphragm.

19. (original) A planar-magnetic transducer as set forth in claim 1 wherein the predetermined distance between at least two of the adjacent high energy magnets is at least seventy five thousandths of an inch.

20. (original) A planar-magnetic transducer as set forth in claim 1 wherein the predetermined distance between at least two of the adjacent high energy magnets is at least ninety thousandths of an inch.

21. (original) A planar-magnetic transducer as set forth in claim 1 wherein the predetermined distance between at least two of the adjacent high energy magnets is at least one hundred and fifty thousandths of an inch.

22. (original) A planar-magnetic transducer as set forth in claim 1 wherein at least two of the adjacent high energy magnets have common dimensions and the predetermined distance therebetween is at least one half the width of one of the magnets.

23. (original) A planar-magnetic transducer as set forth in claim 1, wherein the predetermined distance between the at least two high energy magnets is at least seventy percent of the width of one of the at least two adjacent magnets.

24. (original) A planar-magnetic transducer as set forth in claim 1, wherein the predetermined distance between at least two of the adjacent high energy magnets is at least 100 percent of the width of one of the at least two adjacent magnets.

25. (original) A planar-magnetic transducer as set forth in claim 1, wherein the mounting support structure further includes forward support structure coupled to the mounting support structure and extending across and forward of the diaphragm to eliminate the effect of combined diaphragm tension forces and magnetic attraction forces from potentially reducing the predetermined distance between the adjacent magnets.

26. (original) A planar-magnetic transducer as set forth in claim 1 further comprising:
a rigid covering structure attached to the mounting support structure and having open areas and closed areas which substantially cover one of said first or second surface sides of the diaphragm,

the primary magnetic structure being attached to the mounting support structure and mounted over the first surface side of the diaphragm,

said covering structure open areas having acoustic transparency.

27. (original) A planar-magnetic transducer as set forth in claim 27 wherein said rigid covering structure is ferrous composition and provides magnetic shielding.

28. (original) A planar-magnetic transducer as set forth in claim 27 wherein said rigid covering structure braces the transducer against support structure flexing and very high magnetic forces caused by the adjacently mounted high energy magnets and supports the maintenance of predetermined diaphragm tension calibration.

29. (original) A planar-magnetic transducer as set forth in claim 1 wherein a long term viscous material is applied along at least a portion of a periphery of the vibratable diaphragm and configured to provide damping properties to the diaphragm.

30. (original) A planar-magnetic transducer as set forth in claim 30 wherein application of said viscous material is limited to an area outside of the conductive surface area but extends into the active region of the diaphragm.

31. (original) A planar-magnetic transducer as set forth in claim 30 wherein application of said viscous material is limited to an area of the diaphragm outside and proximate to a last row of magnets on each side of the primary magnetic structure but extends into the active region of the diaphragm.

32. (original) A planar-magnetic transducer as set forth in claim 31, wherein said viscous material is a solvent based polyurethane compound.

33. (original) A planar-magnetic transducer as set forth in claim 1 wherein:
said diaphragm has a central region and lateral regions that are a distance away from said central region,

said primary magnetic structure has central region magnets and lateral magnets that are spaced away from said central region magnets,

the predetermined spaced-apart relationship of the diaphragm from the magnets of the primary magnetic structure being greater at the central region of the diaphragm which is positioned over at least one central magnet than at the lateral diaphragm regions which are positioned over at least one lateral magnet.

34. (original) A planar-magnetic transducer as set forth in claim 1 wherein at least a first of the transducers is optimized for higher frequencies and attached to at least a second of the transducers which is optimized to operate down to a lower frequency than that of said first transducer thereby forming a multiway loudspeaker, said multiway loudspeaker further including at least a high pass crossover filter for driving said first transducer.

35. (previously presented) A planar-magnetic transducer comprising:

at least one thin film vibratable diaphragm with a first surface side and a second surface side, including a predetermined active region, said predetermined active region including a predetermined conductive surface area for converting an input electrical signal into a corresponding acoustic output;

a magnetic structure including at least three elongated magnet rows placed adjacent and substantially parallel to each other with said magnets each being of high energy product greater than 25 mega Gauss Oersteds (MGO); and

a mounting support structure coupled to the primary magnetic structure and the diaphragm to capture the diaphragm, hold it in a predetermined state of tension and space it at a predetermined distance from the primary magnetic structure adjacent one of the surface sides of the film diaphragm;

said conductive surface area including elongate conductive paths running substantially in parallel with said magnets;

the mounting support structure, the diaphragm and the at least three magnets of the primary magnetic structure having coordinated compositions and being cooperatively configured

and positioned in predetermined spaced apart relationships wherein (i) the mounting support structure stabilizes the static and dynamic relationship between the diaphragm and the primary magnetic structure over and between extended periods of use and (ii) concurrently resists the high energy magnetic forces interacting between the at least three magnets which would otherwise interfere with the predetermined tension of the diaphragm;

said planar-magnetic transducer being operable as a single-ended planar- magnetic transducer.

36. (original) A planar-magnetic transducer as set forth in claim 35 wherein the high energy magnets comprise neodymium.

37. (previously presented) A planar-magnetic transducer as set forth in claim 35 wherein the high energy magnets are neodymium magnets with an energy rating of at least 34 MGO.

38. (previously presented) A planar-magnetic transducer comprising:
at least one thin film vibratable diaphragm with a first surface side and a second surface side, including a predetermined active region, said predetermined active region including a predetermined conductive surface area for converting an input electrical signal into a corresponding acoustic output;

a mounting support structure coupled to the primary magnetic structure and the diaphragm to capture the diaphragm, hold it in a predetermined state of tension and space it at a predetermined distance from the primary magnetic structure adjacent one of the surface sides of the film diaphragm; and

primary magnetic structure including at least three high energy, elongated magnets placed adjacent and substantially parallel to each other with each magnet having an energy product of greater than 25 mega Gauss Oersteds (MGO);

said conductive surface area including elongate conductive paths running substantially in parallel with said magnets;

the mounting support structure, the diaphragm and the at least three magnets of the primary magnetic structure being cooperatively configured and positioned in predetermined spaced apart relationships;

at least two of said high energy magnets being adjacently positioned in a predetermined spaced apart relationship wherein adjacent poles of the adjacent magnets have nonshared, localized magnetic loops represented by local loop energy maxima in a plane of the diaphragm which are respectively greater than a shared energy maxima at a central position between the adjacent poles and extending along a shared magnetic loop of the respective adjacent poles in the plane of the diaphragm;

said planar-magnetic transducer being operable as a single-ended planar-magnetic transducer.

39. (original) A planar-magnetic transducer as set forth in claim 38, wherein the predetermined active region has a total surface area of less than 150 square inches, yet generates a high acoustic output having an upper audio bandwidth extending down to a low range audio frequency.

40. (original) A planar-magnetic transducer as set forth in claim 38, further comprising a plurality of adjacently positioned high energy magnets having respective local loop energy maxima, wherein the majority of local loop energy maxima in the plane of the diaphragm have an average value which is greater than an average value of energy levels at the central positions in the plane of the diaphragm between corresponding adjacent poles of the adjacent magnets.

41. (original) A planar-magnetic transducer as set forth in claim 38, wherein the shared energy maxima is no greater than 90 percent of the local loop energy maxima.

42. (original) A planar-magnetic transducer as set forth in claim 38, wherein the shared energy is no greater than 80 percent of the local loop energy.

43. (original) A planar-magnetic transducer as set forth in claim 38, wherein the shared energy is no greater than 75 percent of the local loop energy maxima.

44. (original) A planar-magnetic transducer as set forth in claim 38, wherein a predetermined distance between the local loop energy maxima for adjacent magnets is approximately equal to a separation distance between the corresponding adjacent magnets.

45. (original) A planar-magnetic transducer as set forth in claim 44, wherein the predetermined distance between the local loop energy maxima for adjacent magnets is at least seventy five thousandths of an inch.

46. (original) A planar-magnetic transducer as set forth in claim 45, wherein the predetermined distance between the local loop energy maxima is at least ninety thousandths of an inch.

47. (original) A planar-magnetic transducer as set forth in claim 38 wherein the predetermined distance between the local loop energy maxima is at least 100 percent of the width of the magnets.

48. (original) A planar-magnetic transducer as set forth in claim 38 wherein the predetermined spaced apart relationship between any two of the at least three adjacent, high energy magnets is at least seventy five thousandths of an inch.

49. (original) A planar-magnetic transducer as set forth in claim 38 wherein the predetermined spaced apart relationship between any two of the at least three adjacent, high energy magnets is at least ninety thousandths of an inch.

50. (original) A planar-magnetic transducer as set forth in claim 38 wherein the predetermined spaced-apart relationship between at least two of the at least three adjacent, high energy magnets is at least one hundred and fifty thousandths of an inch.

51. (original) A planar-magnetic transducer as set forth in claim 38 wherein the at least three adjacent, high energy magnets have common dimensions and the predetermined spaced-apart relationship between at least two of said adjacent magnets is at least one half the width of one of the adjacent magnets.

52. (original) A planar-magnetic transducer as set forth in claim 38, wherein the predetermined spaced-apart relationship between at least two of the at least three adjacent, high-energy magnets is at least seventy percent of the width of one of said adjacent magnets.

53. (original) A planar-magnetic transducer as set forth in claim 38 wherein the predetermined spaced-apart relationship between at least two of the at least three adjacent, high-energy magnets is at least 100 percent of the width of one of said adjacent magnets.

54. (previously presented) A planar-magnetic transducer as set forth in claim 38 wherein the high energy magnets are neodymium magnets with an energy rating of at least 34 MGO.

55-58. (canceled)

59. (previously presented) A planar-magnetic transducer comprising:

at least one thin film vibratable diaphragm with a first surface side and a second surface side, including a predetermined active region, said predetermined active region including a predetermined conductive surface area for converting an input electrical signal into a corresponding acoustic output;

primary magnetic structure including at least three elongated magnets placed adjacent and substantially parallel to each other with at least one of said magnets being of high energy with each having an energy product of greater than 25 mega Gauss Oersteds (MGO); and

a mounting support structure coupled to the primary magnetic structure and the diaphragm to capture the diaphragm, hold it in a predetermined state of tension and space it at a predetermined distance from the primary magnetic structure adjacent one surface side of the film diaphragm;

said conductive surface area including elongate conductive paths running substantially in parallel with said magnets;

any of the at least three adjacent magnets being oriented to be of opposite polarity orientation in relation to an adjacent magnet;

said primary magnetic structure having at least three adjacent rows of side by side magnets with at least an outer two rows of the at least three rows of magnets providing less magnetic field strength through the conductive surface area of the diaphragm than provided through the conductive surface areas of the diaphragm by a center row of the magnets;

said planar-magnetic transducer operating as a single-ended planar-magnetic transducer.

60. (original) A planar-magnetic transducer as set forth in claim 59 including at least five adjacent rows of magnets with at least two outer rows of said five rows of magnets providing less magnetic field strength through the conductive surface area of the diaphragm than provided through the conductive surface area of the diaphragm by a center row of magnets.

61. (previously presented) A planar-magnetic transducer as set forth in claim 59 wherein the primary magnetic structure includes neodymium magnets with an energy rating of at least 34 MGO.

62. (original) A planar-magnetic transducer as set forth in claim 59 wherein:
said diaphragm has a central region and lateral regions that are a distance away from said central region,

said primary magnetic structure has central region magnets and adjacent lateral magnets that are spaced away from said central region magnets,

the predetermined spaced apart relationship of the diaphragm from the magnets of the primary magnetic structure being greater at a central region of the diaphragm over at least one central magnet than at the lateral regions over at least one lateral magnet.

63-83. (canceled)

84. (previously presented) A planar-magnetic transducer comprising:

at least one thin film vibratable diaphragm with a first surface side and a second surface side, including a predetermined active region, said predetermined active region including predetermined, elongate conductive surface areas formed of a plurality of conductive elements for converting an input electrical signal into a corresponding acoustic output;

a mounting support structure coupled to the primary magnetic structure and the diaphragm to capture the diaphragm, hold it in a predetermined state of tension and space it at a predetermined distance from the primary magnetic structure adjacent one of the surface sides of the film diaphragm; and

primary magnetic structure including at least three high energy, elongated magnets placed adjacent and substantially parallel to each other with each magnet having an energy product of greater than 25 mega Gauss Oersteds (MGO);

at least two of said high energy magnets being adjacently positioned in a predetermined spaced apart relationship wherein adjacent poles of the adjacent magnets have nonshared, localized magnetic loops represented by local loop energy maxima as well as shared magnetic loops between the respective adjacent poles of the high energy magnets;

said conductive surface area running substantially parallel to said magnets and more proximate to the local loops of the high energy magnets than to a center point of the shared magnetic loops between the adjacent magnets;

said planar-magnetic transducer being operable as a single-ended planar-magnetic transducer.

85. (original) A transducer as set forth in claim 84, wherein the conductive elements are substantially parallel to the elongated magnets and the conductive surface areas are most proximate to the respective local loop energy maxima associated with an adjacent magnet.

86. (previously presented) A planar-magnetic transducer as set forth in claim 84 wherein the high energy magnets are neodymium magnets with an energy rating of at least 34 MGO.

87. (original) The transducer of claim 84, wherein the respective conductive surface areas are approximately centered over the local loops of adjacent high energy magnets.